


Main Features

Comprehensive safety guarantee, combined with anti-corrosion capability

The furnace cavity is made of Grade 316L stainless steel, with a warranty of 5 years. The 3D adjustable, explosion-proof security door, installed with buffer and choke (to prevent microwave leakage), is self-sealing, impact-resistant and with interlocking linkage mechanism. The aerospace composite fiber outer vessel, wholly sprayed with PFA coating, boasts both higher anti-corrosion and higher pressure-resistance levels, compared to those of PEEK materials. The 70MPa pressure-resistance and the 600 ° C heat-resistance capabilities guarantee the safe operation of users under extreme conditions.



Dual magnetron inverter control system ensures consistent sample digestion

SUPER-455

Microwave Digestion Workstation adopts dual magnetron inverter control system and high-frequency closed-loop PID control, thereby realizing microwave continuous non-pulse output, more uniform microwave field in the cavity, higher energy utilization rate, and consistent sample digestion.



Two LCD screen, displaying real-time operation and experiment status

The 7-inch color LCD touch screen displays real-time data, such as temperature, power, time, and steps. Swift switch to display of coordinate curves greatly facilitates users to better know what is going on with the experiment. The 5-inch color LCD screen allows clear, real-time observation of operation inside the furnace cavity. Equipped with interfaces, such as USB, network port or Wi-Fi, the vessel, once permitted, can be remotely operated and monitored through computer or Pad.

Full-vessel pressure control technology

The high-pressure digestion vessel adopts elastic pressure relief and self-sealing technology. Under normal operation conditions, the vessel is completely sealed without leakage. Under overpressure conditions, the pressure is automatically and safely released together with excessive reaction gas (CO₂ and nitrogen oxides); then, it is immediately sealed, ensuring smooth progress of subsequent experiments.




Full-vessel precise temperature control and monitoring, ensuring safety and digestion performance

Non-contact mid-infrared sensors at bottom monitor and visualize real-time temperature change of sample solution inside each digestion vessel. The whole vessel temperature control system effectively monitors abnormal conditions during digestion experiment. Once abnormal temperature is detected, the vessel immediately stops microwave emission and starts to sound the alarm, so that experimental safety is not disturbed.



Smart software operation, conforming to FDA21CFRPart11

The vessel, running on the Android operating system, is convenient and multi-functional. It offers many functions, such as electronic signature, hierarchical permission and audit trail, all in conformity with relevant regulations of FDA21CFRPart11. The software automatically identifies model of the turntable and automatically counts the number of vessels, making the experiment easier and faster, with the absence of tedious manual counting and input.



Various supporting tools, making experiment easy and convenient


Various tools are supplied to reduce workload for operators and improve the work efficiency of sample preparation. For example, a mobile and flexible tool trolley is able to transfer rotor loaded with sample into and out of furnace cavity, avoiding direct contact between operator and digestion vessel for safety concerns.



SUPER-455 Microwave Digestion Workstation Parameters:



Power	220~240VAC50/60Hz20A
Working environment temperature	0~40°C
Relative humidity for working environment	15~80%RH
Microwave source	2450MHz; Maximum microwave output power 2000W, emitted from Dual magnetron inverter high-energy microwave field; non-pulse continuous microwave output
Installed power	3800W
Microwave cavity	Grade 316L stainless steel microwave resonant cavity, with a wall thickness of more than 3mm, sprayed with multi-layer PFA coating
Furnace exhaust system	Automatically adjusted air volume; cooling to room temperature in less than 15 minutes
Software system	Android operating system (8G memory), built-in video SOP, application method library, electronic door lock, etc.
Overall physical size/net weight	600×685×660 (W*D*H) /62kg

Batch amount	24 vessels	40 vessels
Inner vessel material	TFM	TFM
Outer vessel material	Aerospace composite fiber	Aerospace composite fiber with TEFLON coating
Inner vessel volume	110mL	55mL
Maximum temperature	300°C	300°C
Maximum pressure	15Mpa	15Mpa



Wide range of applications

Microwave digestion technology heats reagents and samples in closed containers through microwave penetration and activation. It greatly speeds up reaction and shortens sample preparation time, with increased pressure and reaction temperature in digestion vessel. Microwave digestion is a commonly seen digestion technology widely applied in many fields.



NO.	Sample mass/g	Cd concentration /ng·mL ⁻¹	Cd content /ng·g ⁻¹	RSD/%	
1	1.01034	1.562	38.65	1.4252	
2	1.01257	1.480	36.54	1.1046	
3	1.01083	1.457	35.97	1.0832	
4	1.01256	1.529	37.75	1.1430	
5	1.01155	1.533	37.85	1.3106	
6	1.01281	1.526	37.68	1.0844	
Mean value		1.515	37.40	—	
RSD/%		3.9			
Spike recovery	Spike amount /ng·mL ⁻¹	Recovery rate /%	Measured value /ng·mL ⁻¹	Standard value /ng·mL ⁻¹	Uncertainty /ng·mL ⁻¹
	1	0.4	98.75	74	3
	2	0.6	97.00		
	3	0.8	92.88		
4	1.0	93.4			